

Hana

compact acoustic booth

Technical Data

- Top panel: outside - MDF 28 mm, upholstered, colour: LDS27 - black; inside - chipboard 12 mm upholstered, colour: LDS27 - black, two-point lighting; exhaust fan activated by a motion detector (adjustable ventilation speed); ventilation grate in the floor;
- Body - 58 mm, upholstered walls with acoustic filling;
- Shelf - MDF board 28 mm, lacquered, measurements: 1070 x 388 x 28 x 28 mm, colour: black;
- Mediabox - 2x230V + 1xUSB + 1xUSB type C;
- Rotary knob - powder coated steel, colour: black;
- Door - toughened glass 8 mm, clear;
- Bottom rim: outside - MDF 28 mm, upholstered, colour: LDS27 - black; inside - chipboard 18 mm, carpet, colour: graphite;
- Electric hook-up. Electric systems available: EU, USA, Schuki, UK, Ch;
- Additional information: Sonic technology structure with A-class acoustics certificate; automatic light switch simultaneously activating the ventilation system; 2 fans: 1 intake and 1 exhaust; volume 14dB, efficiency 90m³/h;
- Dimensions: 1132 x 1184 mm, h. 2199

Selected configuration

HN01

Height: 2217 mm

Width: 1092 mm

Length: 1184 mm

Colour 1: M-63017 Rusty

Colour 2: M-66010 Blue

Type of plug: EU plug

Sustainability



Guarantee

.mdd products - 5 years.

Electrical components - 2 years.

Assembly manuals



Certificates



- Sustainable production – we are not indifferent to the environmental impact of our furniture, therefore we provide the essential information on the life cycle of our products through the Environmental Product Declarations (EPD).
-

Material composition

- MFC: 76%
- Wood: 5%
- Steel: 5%
- Glass: 8%
- Plastic: 3%
- Fabric: 2%
- Polyurethane foam: 2%

*average values for a representative of the group.

Recycled content

9%

Recyclability

- Recycling: 12%
- Downcycling: 88%

*average values for a representative of the group.

Packaging


Materials: cardboard + foil + wooden crate

Recyclability: 100%

Fabric technical data

M-63017 Rusty

Material	100% polyester
Weight	364g/m2 • 510g/lm
Abrasion resistance rubs	75,000 Martindale cycles; 100,000 double rubs wyzenbeek ASTM D4157
Pilling resistance	scale 1-5, max 5 • EN ISO 12945-2 4
Colour fastness to light	scale 1-8, max 8 • EN ISO 105 - B02 5-7
Colour fastness to rubbing	scale 1-5, max 5 • EN ISO 105x12 (wet/dry) 4-5/4-5
Acoustic test sound absorption	ISO 354
Flammability	BS EN 1021 - 1:2006 (cigarette), BS EN 1021 - 2:2006 California Bulletin CAL 117-E-Class 1
Fabric manufacturer's warranty	10 years

M-66010 Blue

Material	100% polyester
Weight	364g/m2 • 510g/lm
Abrasion resistance rubs	75,000 Martindale cycles; 100,000 double rubs wyzenbeek ASTM D4157
Pilling resistance	scale 1-5, max 5 • EN ISO 12945-2 4
Colour fastness to light	scale 1-8, max 8 • EN ISO 105 - B02 5-7
Colour fastness to rubbing	scale 1-5, max 5 • EN ISO 105x12 (wet/dry) 4-5/4-5
Acoustic test sound absorption	ISO 354
Flammability	BS EN 1021 - 1:2006 (cigarette), BS EN 1021 - 2:2006 California Bulletin CAL 117-E-Class 1
Fabric manufacturer's warranty	10 years